# 30" Grill, Non Rotis, LP Gas

Series 7					
Stainless Steel	I	LPG			



DCS Outdoor Grills are simply the most advanced grilling system available for on-cart or built in applications. At DCS we combine the latest grilling technology and innovation to deliver the ultimate in outdoor cooking performance and control. Every DCS Grill is handcrafted and constructed entirely of heavy gauge type 304 stainless steel. Available in Natural and LP Gas. Grill Cart pictured sold separately.

# DIMENSIONS

Height	24 1/4 "
Width	30 "
Depth	26 5/8 "

# FEATURES & BENEFITS

#### Stainless Steel Burners

The precision ported U-shaped stainless steel burners are rated at a massive 25,000BTU each, offering premium quality and performance. A heat shield directs heat upwards maximizing heating efficiency.

#### Ceramic Radiant Technology

A layer of ceramic rods provides intense yet even heat. It gives a consistent grilling surface, with controlled heat rather than direct fire.

#### Precision heat and control

A DCS Grill puts you in control of up to a massive 50,000 BTU per hour total power. That power lets you choose the precise heat you need from a low and slow 300° up to an intense 1100°. DCS Grills do more than help you grill an incredible steak, you can close the specially designed hood and use the power of convection to cook the perfect pizza. DCS Grills put you in control, giving you the versatility to cook what you want.

#### Drip Pan

DCS Grills feature a removable drip pan, conveniently located in a slide-out tray to allow for easy cleaning.

#### **Full Surface Searing**

This grill features full surface searing, rather than uneven hotspots.

### SPECIFICATIONS



# Accessories (sold separately) Insulated jacket BGB30-IJS Optional cart mount CAD1-30 / BGB30-CSS Burners Number of U-burners 2 **Cooking Surface Area** Primary cooking area 553sq. in. Total cooking area 748sq. in. 195sq. in. Warming rack area Features Full surface searing Ignition system Spark Warming rack Finish Material 304 grade stainless steel Weather resistant Gas requirements 1/2" NPT male with 3/8" in flare LP Gas type LP hose with regulator and **Operational pressure** 11" W.C. Supply Pressure 12" to 14" W.C.

Installation dimensions

#### QUICK REFERENCE GUIDE > BGC30-BQ-L

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	28 1/2 "
Insulated jacket for proud cut-	Varies - check manual "
Performance	
Griddle power in BTU	25000
Total Power in BTU	50000
Power requirements	
Grill power supply	9V battery for igntion
Product dimensions	
Depth	26 5/8 "
Height	24 1/4 "
Width	30 "
Warranty	
Parts and labor	2 years

## Other product downloads available at dcsappliances.com

- Service & Warranty Booklet
  - User Guide

↓

↓

≁

71124

- Installation Guide
- Data Sheet
- ✓ CAD File

## A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support
T 1.888.936.7872 Wwww.dcsappliances.com

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. PDCS by Fisher & Paykel Appliances Limited 2020

SKU