QUICK REFERENCE GUIDE > BH1-48RS-L Date: 10.02.2021 > 1

48" Grill, Rotisserie and Side Burners, LP Gas

Series 7

Stainless Steel | LPG



Designed with flexibility in mind, DCS Grills allow you to cook a wide variety of meals and are engineered to deliver the functionality and power demanded by a professional chef. DCS Grills are hand-finished to perfection to complement the quality of the DCS premium outdoor kitchen and built to withstand the demands of the serious cook and the extremes of mother nature. Available in Natural and LP Gas. Grill Cart pictured sold separately.

DIMENSIONS

| Height | 24 1/4 |
|--------|--------|
| Width | 47 7/8 |
| Depth | 26 5/8 |

FEATURES & BENEFITS

Precision heat and control

A DCS Grill puts you in control of up to a massive 126,500 BTU per hour total power. That power lets you choose the precise heat you need from a low and slow 300° up to an intense 1100°. DCS Grills do more than help you grill an incredible steak, you can infuse smoke into your favorite meal using the built in smoker, or close the specially designed hood and use the power of convection to cook the perfect pizza. DCS Grills put you in control, giving you the versatility to cook what you want.

Double-sided Cast Stainless Steel Grates

One side has a gentle radius for handling delicate foods. The other side is W-shaped for perfect sear lines while channeling oil away to an easily removable drip tray.

Grease Management System™ Grease Channeling Technology

This patented technology reduces flare-ups by directing grease and oils away from the burner flames during grilling.

Smart Beam™ Grill Light

A halogen light is designed to illuminate the entire cooking surface for perfect night grilling.

Temperature Gauge - zero to sear

Go from zero to sear with DCS Grills' new built-in temperature gauge. It lets you know exactly how hot the grill is, even when the hood is down.

Dedicated Sealed Smoker

A dedicated smoker tray with a direct 3,500BTU burner offering a clean, convenient option for specialized smoking recipes.

SPECIFICATIONS

Side burners

| Accessories (sold separately) | |
|-------------------------------|-------------|
| Griddle plate | BGC-GP |
| Hybrid IR burner | BGC-IR |
| Insulated jacket | BGA48-IJS |
| Optional cart mount | CAD1-48 |
| Burners | |
| Number of U-burners | 3 |
| Number of side burners | 2 |
| Cooking Surface Area | |
| Primary cooking area | 630sq. in. |
| Side burner area | 244 sq. in. |
| Total cooking area | 1115sq. in. |
| Warming rack area | 241sq. in. |
| Features | |
| Double sided Stainless Steel | • |
| Full surface searing | • |
| Grease management system™ | • |
| Hood temperature gauge | • |
| Ignition system | Spark |
| Metal dials | • |
| Rotisserie | |
| Ciala la coma a con | |



QUICK REFERENCE GUIDE > BH1-48RS-L

Date: 10.02.2021 > 2

| Smoker | • |
|---|---|
| Warming rack | |
| Finish | |
| | |
| Material | 304 grade stainless steel |
| Weather resistant | • |
| Gas requirements | |
| 1/2" NPT male with 3/8" in flare | • |
| Gas type | LP |
| LP hose with regulator and | • |
| Operational pressure | 11" W.C. |
| Supply Pressure | 12" to 14" W.C. |
| | |
| Installation dimensions | |
| Installation dimensions Cutout depth (proud) | 22 3/4 " |
| | 22 3/4 " 10 1/8 " |
| Cutout depth (proud) | |
| Cutout depth (proud) Cutout height (proud) | 10 1/8 " |
| Cutout depth (proud) Cutout height (proud) Cutout width (proud) | 10 1/8 " 45 3/4 " |
| Cutout depth (proud) Cutout height (proud) Cutout width (proud) Insulated jacket for proud cut- | 10 1/8 " 45 3/4 " |
| Cutout depth (proud) Cutout height (proud) Cutout width (proud) Insulated jacket for proud cut- | 10 1/8 " 45 3/4 " Varies - check manual " |
| Cutout depth (proud) Cutout height (proud) Cutout width (proud) Insulated jacket for proud cut- Performance Griddle power in BTU | 10 1/8 " 45 3/4 " Varies - check manual " |
| Cutout depth (proud) Cutout height (proud) Cutout width (proud) Insulated jacket for proud cut- Performance Griddle power in BTU Rotisserie burner power in BTU | 10 1/8 " 45 3/4 " Varies - check manual " 25000 14000 |
| Cutout depth (proud) Cutout height (proud) Cutout width (proud) Insulated jacket for proud cut- Performance Griddle power in BTU Rotisserie burner power in BTU Side burner power in BTU | 10 1/8 " 45 3/4 " Varies - check manual " 25000 14000 |

9V battery for ignition

Power requirements

Grill power supply

| Rotisserie power supply | 120V 60Hz |
|-------------------------|-----------|
| Product dimensions | |
| Depth | 26 5/8 " |
| Height | 24 1/4 " |
| Width | 47 7/8 " |
| Warranty | |
| Parts and labor | 2 years |
| SKU | 71298 |

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. PDCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com

Service & Warranty Booklet



User Guide



Installation Guide



CAD File

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.dcsappliances.com

