PROFESSIONAL® SERIES











FEATURES & BENEFITS

- 27" in depth, a perfect companion to Pro Grand® Professional Ranges
- ★- Equipped with the Thermador Connected Experience by Home Connect™
 - Powerfully Quiet® system accepts integral, inline, and remote blowers
 - Keep food warm until it's ready to be served with two independently controlled infrared heat lamps
 - Beautiful illumination with multi-level, vivid LED lights

ACCESSORIES (OPTIONAL)

25 ft. Blower Connector Cable - EXTNCB25W

EXTNCB25W - For use with the following inline and remote blowers: VTR630W, VTR1030W, VTR1330W, VTI610W, VTI1010W

Roofplates


RFPLT600P - For use with 600 CFM remote blower VTR630W

RFPLT1000P - For use with 1000 CFM remote blower VTR1030W and 1300 CFM blower VTR1330W

6" Tall Duct Cover, 36" Wide	DC366W		
8' - 9' Ceiling Telescoping Duct Cover, 36" Wide	DC3689W		
10' - 12' Ceiling Telescoping Duct Cover, 36" Wide	DC361012W		

Built-In Remote Control Panel

REMCPW - Ability to vertically install on cabinetry or wall to control hood in a convenient location



GENERAL PROPERTIES

Features

Multi-Level LED Lights with Fading Transitions, Infrared Heat Lamps, Automatic Mode, Check Filter Reminder Light, Delay Shut-Off

5 ,	,			
Operating Mode	Ducted			
Number of Speed Settings	4-Stage			
Motor Location	Blower (Sold Separately)			
Number Of Lights	2			
Bulb Type	LED			
Light Lumens	100 – 150			
Light Color (°K)	3500 – 4000			
Total Power Of The Lamps (W)	2.4			
Damper Included	Yes			
Grease Filter Material	Washable Stainless Steel			
Grease Filter Type	Stainless-Steel Commercial Style Baffle Filter			
Home Connect™ (Wi-Fi Enabled)	Yes			
TECHNICAL DETAILS				
Watts (W)	See Chart on Page 3			
Current (A)	See Chart on Page 3			
Volts (V)	120 V			
Frequency (Hz)	60 Hz			
Plug Type	120V-3 Prong			
DIMENSIONS & WEIGHT				
Overall Appliance Dimensions (Width Of Canopy Included) (HxWxD) (in)	18" x 35 15 / 16 " x 27"			
Minimum Required Distance Above Gas / Electric Cooking Surface	30" / 30"			
Diameter of Air Duct (in) Top	10"			
Diameter of Air Duct (in) Back	10"			
Net Weight (lbs)	80 lbs			
ACCECCODIES (DECUMPED)				

ACCESSORIES (REQUIRED)

Blower (Sold Separately)


, , , , , , , , , , , , , , , , , , , ,						
BLOWER OPTIONS						
Remote Blower (Mounted to Roof or External Wall)	VTR630W - 600 CFM					
	VTR1030W - 1000 CFM					
	VTR1330W - 1300 CFM					
Inline Blower (Mounted Between Kitchen and External Wall)	VTI610W - 600 CFM					
	VTI1010W - 1000 CFM					
Integrated Blower (Mounted in Hood)	VTN630W - 600 CFM					
	VTN1090R - 1000 CFM					
WARRANTY						
Limited Warranty Parts And Labor	2 Year					



Page 1 of 5 3 / 20



PROFESSIONAL® SERIES




OPTIONAL ACCESSORIES

36" WIDE DUCT COVER

Stainless steel duct cover for wall hood applications






DC3689W TELESCOPING FOR 8'-9' CEILINGS




measurements in inches (mm)



DC361012W TELESCOPING FOR 10'-12' CEILINGS



measurements in inches (mm)



REMOTE CONTROL PANEL REMCPW



Convenience at your fingertips: The remote control accessory offers the freedom to extend your hood controls to a more reachable spot


Page 2 of 5 3 / 20



			ELECTRIC LOAD						
MODEL	DESCRIPTION		VTN630W	VTN1090R	VTI610W	VTI1010W	VTR630W	VTR1030W	VTR1330W
PH36GWS	36" Grand Wall Hood	Amps	9.2	12.6	11.1	13.0	11.1	13.0	16.5
		Watts	1,104	1,512	1,332	1,560	1,332	1,560	1,980


REMOTE BLOWERS (MOUNTED TO ROOF OR EXTERNAL WALL)

VTR630W-600 CFM




measurements in inches and mm

VTR1030W-1000 CFM



measurements in inches and mm

VTR1330W-1300 CFM



measurements in inches and mm


Page 3 of 5 3 / 20

PH36GWS 27-INCH DEPTH WALL HOOD (36-INCH WIDTH) **PROFESSIONAL® SERIES**




INLINE BLOWERS (MOUNTED BETWEEN KITCHEN AND EXTERNAL WALL)

VTI610W-600 CFM



measurements in inches and mm


VTI1010W-1000 CFM




measurements in inches and mm

INTEGRATED BLOWERS (MOUNTED IN HOOD)

VTN630W-600 CFM



VTN1090R-1000 CFM




Page 4 of 5 3 / 20




REMOTE BLOWER ACCESSORIES

ROOFPLATE-RFPLT600P

PROFESSIONAL® SERIES



ROOFPLATE-RFPLT1000P



EXTNCB25W

For use with the following Inline and Remote Blowers: VTR630W, VTR1030W, VTR1330W, VTI610W, VTI1010W

These warranties give you specific legal rights and you may have other rights that vary from state to state. Full warranty and limited warranty from date of installation. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.

1 800 735 4328 | USA THERMADOR.COM | CANADA THERMADOR.CA | ©2020 BSH HOME APPLIANCES CORPORATION. ALL RIGHTS RESERVED.

Page 5 of 5 3 / 20